

微电脑环压/边压强度试验机
Microcomputer Edge crush & Ring crush tester series



■ 本设备参数、功能符合以下国家标准

- 1、GB/T 2679-1995 (纸和纸板环压强度的测定) (Determination of compressive strength of paper and board)
- 2、GB/T 6548-1998 (瓦楞纸板边压强度的测定) (Determination of corrugated cardboard marginal pressure strength)
- 3、GB/T 6546-1998 (瓦楞纸板粘合强度的测定) (Determination of the bonding strength of corrugated board)
- 4、GB/T 2679.6-1996 (瓦楞原纸平压强度的测定) (Corrugated cardboard crush strength determination)

■ 主要技术参数 The main technical parameters

型号 Model	HD-A513-A	HD-A513-B
容量 Capacity	10,20,50,100,200kgf	200,500kgf
解析度 Resolution	1/100,000	1/250,000
精度 Precision	≤0.2%	≤0.1%
电机/ motor	直流电机DC motor	伺服电机Servo motor
显示方式 Display method	面板控制, LED液晶屏显示+电脑式采用 HD-001A电脑系统软件控制, windows模式操作+可显示多种测试曲线图、矩形图 Panel control, LED display+ HD-001A computer systems software control, windows operation+ display various test curve and histogram Time + strength display	面板控制, LED液晶屏显示+电脑式采用 TM2101电脑系统软件控制, windows模式操作+可显示多种测试曲线图 带位移显示,位移+力量显示; 时间+力量显示 Panel control LED display+TM2101 computer systems software control, windows operation+ display various test curve Display Displacement displacement+ strength display; Time + strength display
压板 Platen	直径118mm或视平压试样直径而定 100 × 100mm or Depending on the diameter of the flat crush sample.	
压缩间距 Compressed spacing	80mm	80mm
压板平行度 Platen parallelism	±0.05mm	±0.05mm
环压试样 Ring crush sample	100 × 25mm	
边压粘合试样 Ring crush sample	25 × 100mm	
测试速度 Test speed	(10 ± 3) mm/min	
外形尺寸 Outside Dimension(L*W*H)mm	480 × 460 × 550mm	480 × 460 × 550mm
机台重量 Weight	70 kg	75kg
电源 Power	1 φ, 220V, 50Hz, 2A	

